

*Our premium product line:
your best choice for top quality*

REISSER PREMIUM PRODUCT
YOUR BEST

REISSER

Aerated concrete screws

just like fixing into wood

REISSER HIGH QUALITY PRODUCT
HIGH LEVEL

- DNS®
- DRIBO® A4 terrace screws
- CABRI® terrace screws
- TS terrace screws
- DRIBO®
- Hardwood screws
- Solid wood decking screws
- Tongue and groove screws
- STRONGI®
- Distance set

Additional uses for the manufacturer thanks to:

- Special thread geometry
- Special materials
- Special coatings
- Special screw types
- Special packaging



REISSER-Schraubentechnik GmbH
Fritz-Müller-Str. 10
D-74653 Ingelfingen-Criesbach

Fon: +49-(0)7940-127-0
Fax: +49-(0)7940-127-49
e-mail: info@reisser-screws.com

www.reisser-screws.com




REISSER Aerated concrete screws

Perfect for temporary fastenings

- After disassembly, no plugs remain visible
- Less damage to the wall

Quick assembly!

- thanks to the large thread lead
- No pre-drilling required – the screw forms its own supporting thread by itself. Pre-drilling can increase the working load.



Secure and durable

- improved corrosion protection due to blue zinc coating

Better hold !

- due to larger thread depth



A neat surface – faster!

- Milled ridges underneath head create perfect countersunk in wood
- No pre-countersunk required



Field of application

For fastening substrates and wooden, metal or plastic covers (insulation materials, wooden slats, metal profiles and cable ducts)

Recommended use

The aerated concrete substrate can be treated almost like wood. When using a screwdriver (battery-powered or 220V), a screw-in test must be performed due to the highly variable strength of the concrete precision block and ceiling panels. The friction clutch of the screwdriver must be activated as soon as the screw head is flush with the part to be fastened. Do not use an impact screwdriver!

Suitable materials: aerated concrete strength class \geq PP2.

